



RV Products Division

DATA INQUIRY SHEET
46413-812
PARK PAC

Capacity (Nominal BTUH)	Cooling –13,500
Electrical Rating	115 VAC, 60 HZ, 1 Phase
Cooling Full Load AMP's at A.R.I. Standard Condition	Compressor 11.9 Fan Motor (Outdoor – 1.9, Indoor 1.8) Total 15.6
Running Watts (cooling) A.R.I. Standard Condition (80 F. DB 67 F. WB Indoor, 95 F. DB Outdoor)	1700
Running Watts (cooling) A.R.I. Maximum Condition (100 F. DB 72 F. WB Indoor, 120F. DB Outdoor)	2020
Compressor Locked Rotor Amps	63
Metering Device	Capillary Tube
Refrigerant Charge (R-410A)	24.50 oz.
Evaporator Air Delivery (CFM)	535 – High Speed
Generator Size	See "Generators" Below
Unit Weight (pounds) Heat/Cool	116 lbs.
Use time delay fuses or circuit breaker (U.L. H.A.C.R. Type C.S.A.) Rated at 20 amps Supply wires 12 AWG Min. (Copper)	

ACCESSORIES: 8330A3241 Digital Mercury-Free, Non-Programmable Electronic Thermostat
6633-6151 Duct Collar Package

GENERATORS:

It is not the policy of Airxcel, Inc. to size generators for application in Recreation Vehicles or related structures. However, when sizing generators, the total electrical power consumption in Watts must be determined and taken into consideration, such as:

- A. Maximum running watts of the air conditioner at Airxcel, Inc. Desert Test (See Specifications).
- B. Power consumption of electronic ovens, toasters, coffeemakers, television sets, refrigerators, lights, etc.
- C. Generators do lose capacity under the following conditions: (1) Altitude increases above sea level, (2) Temperature increases above certain outdoor design temperatures, and (3) Lack of maintenance.

Airxcel, Inc.
RV Products Division
P.O. Box 4020
Wichita, KS 67204